

Intellektual bloklagich ICE-2



- Barcha foydalanuvchilar uchun aniq va oson bloklash
- Ko'p qirrali va qulay tahrirlash funksiyalari
- Xotira hajmi va ma'lumotlarni boshqarish orqali aqlliroq ish jarayoni

Texnik xususiyatlari

Linza o'lchami	Linza diametri: $\varnothing 110$ mm va undan kam
Joylashtirish diapazoni	FPD: 30.00 dan 99.50 mm gacha; PD (yoki 1/2 PD): 30.00 dan 99.50 mm gacha (15.00 dan 49.75 mm gacha); optik markaz balandligi: -15.0 dan 15.0 mm gacha; o'lcham sozlash: -9.95 dan 9.95 mm gacha; WD: 15.0 dan 45.0 mm gacha; EP: -6.0 dan 6.0 mm gacha
Kiritiladigan ma'lumotlar	FPD (yoki DBL); PD (yoki 1/2 PD); optik markaz balandligi (oprava markazi, BT balandligi, PD balandligi); EP (progressiv linza uzoqqa ko'rish nuqtasi balandligi); shakl o'lchami; linza materiali (CR-39, Hi-index, polikarbonat, akril, Trivex, uretan, shisha); oprava turi (metall, plastik, Optyl, ikki nuqtali, Nylor); ishlov rejimi (Auto, Guide, HC Auto, HC Guide, Step Auto, Step Guide, Flat); linza turi (bir fokusli, ko'p fokusli, progressiv, demo linza); ish kodi
Shakl tasvirlagich (shape imager)	O'lchash diapazoni: 65.5 x 49.0 mm (± 1.5 mm)
Teshik muharriri (hole editor)	Teshik o'rni: 0.01 mm qadam; teshik diametri: $\varnothing 0.50$ dan 10.00 mm gacha (0.01 mm qadam)
Ma'lumotlar xotirasi sig'imi	60 000 ta ma'lumot (barqaror ishlash uchun tavsiya etiladi)
Bloklash usuli	Qo'lda bloklash
Display	8.4 dyuymli SVGA rangli LCD sensorli panel
Interfeys	RS-232C: 4 ta port (1 tasi birinchi linza stanogi yoki server kompyuter uchun, 1 tasi ikkinchi linza stanogi uchun, 1 tasi treyser uchun, 1 tasi shtrix-kod skaneri uchun); LAN: 1 ta port; USB: 1 ta port
Quvvat manbai	AC 100–240 V, 50/60 Gts
Quvvat sarfi	60 VA
O'lchamlari/massasi	224.5(K) x 411(Ch) x 437.5(B) mm / 10.5 kg (8.8 x 16.2 x 17.2" / 23.2 lbs.)
Standart aksessuarlar	Shakl o'lchash stoli, linza stoli (standart), kichik diametrli linza stoli, stilus qalam, qalpoqcha, vint, soyalovchi qopqoq, ferrit o'zak, lagan ushlagich yostiqcha, kosacha va yostiqchalar qutisi, LAN kabeli (kross), quvvat kabeli
Qo'shimcha aksessuarlar	Tashqi shtrix-kod skaneri, USB flesh-disk, WECO kosacha ushlagich, moslashuvchan joylashtirish sozlagichi R/L, shpatel, maxsus loy, RS-232C kabeli