

Sun'iy yo'ldosh treyser LT-1200



- Avtomatik 3D binokulyar treysing
- O'zgaruvchan tayanch nuqtali stilus
- Kompleks treysing (composite tracing)
- Takomillashgan shakl muharriri funksiyasi
- Ko'p funktsiyali laboratoriya treyseri va veb-treyser

Texnik xususiyatlari

Treysing usuli	Avtomatik 3D binokulyar treysing
O'lchanadigan ko'rsatkichlar	Linza shakli; FPD; 3D aylana uzunligi (shablon va demo linza treysingida 2D aylana); oprava egilish burchagi; oprava egriligi
O'lchash nuqtalari	1 000 nuqta
Opravani mahkamlash	Bir tugmali avtomatik mahkamlash
Stilus sozlamasi	Avtomatik va yarim avtomatik rejimlar o'rtasida almashtiriladi
Treysing vaqti: oprava	30 soniya va undan kam (kalibrlash moslamasi yordamida avtomatik binokulyar treysing)
Treysing vaqti: shablon	20 soniya va undan kam (kalibrlash moslamasi yordamida treysing)
Quvvat manbai	AC 100–120 V / 230 V, 50/60 Gts
Quvvat sarfi	70 VA
Kiritiladigan ma'lumotlar	FPD: 30.00 dan 99.50 mm gacha (0.01 mm qadam); PD: 30.00 dan 99.50 mm gacha (0.01 mm qadam); 1/2 PD: 15.00 dan 49.75 mm gacha (0.01 mm qadam); optik markaz balandligi: 0 dan ± 15.00 mm gacha (0.01 mm qadam); o'lchamni sozlash: 0 dan ± 9.95 mm gacha (0.01 mm qadam); o'q: 0 dan 180° gacha (1° qadam); linza materiali (CR-39, Hi-index, polikarbonat, akril, Trivex, uretan, shisha); linza turi (bir fokusli, bifokal, progressiv); oprava turi (metall, plastik, Optyl, ikki nuqtali, Nylor); ishlov rejimi (silliqlashni tanlash, ariqchani tanlash, optik yoki oprava markazini tanlash, shlifovkani tanlash); oprava egilish burchagi: 0 dan 25.5° gacha yoki 0 dan 35.0° gacha (0.1° qadam); oprava egriligi: 0 dan 12.0 gacha (0.1 qadam); ish kodi
Display	10.4 dyuymli rangli LCD sensorli panel
Interfeys	RS-232C: 2 ta port (1 tasi shtrix-kod skaneri uchun, 1 tasi kompyuter yoki linza stanogi uchun); USB: 1 ta port; LAN: 1 ta port
O'lchamlari/massasi	320(K) x 320(Ch) x 480(B) mm / 14 kg (12.6 x 12.6 x 18.9" / 31 lbs.)
Standart aksessuarlar	Aksessuarlar qutisi, ehtiyot saqlagich, olti qirrali kalit, stilus g'ilofi, standart shablon, shablon o'rnatish bloki, standart oprava, oprava tayanch qo'shimchasi, stilus qalam, Windows uchun USB drayver CD, RS-232C kabeli (3 m), USB kabeli (1 m), quvvat kabeli
Qo'shimcha aksessuarlar	Shtrix-kod skaneri, RS-232C kabeli (5 m, 10 m), USB kabeli (3 m, 5 m)

O'lchash diapazoni

Oprava: shakl kengligi	36 dan 85 mm gacha
Oprava: shakl balandligi	18.4 dan 66 mm gacha
Oprava: gorizontal kengligi	113 dan 180 mm gacha
Oprava: qisqich o'rtasidan maksimal balandlik	23 mm
Oprava: maksimal vertikal kenglik	Maksimal balandlikda 50 mm
Oprava: maksimal gorizontal kenglik	Maksimal balandlikda 150 mm
Shablon	ø22 dan 74 mm gacha (vertikal bo'yicha 15.5 dan 66 mm gacha)

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app