

Sun'iy yo'ldosh treyser LT-980



- Avtomatik 3D binokulyar treysing
- O'zgaruvchan tayanch nuqtali stilus
- Chiqindilardan o'rnatilgan himoya
- Bir tugmali demo linza ushlagichi
- Aksessuarlar uchun o'rnatilgan saqlash joyi

Texnik xususiyatlari

Treysing usuli	Avtomatik 3D binokulyar treysing
O'lchanadigan ko'rsatkichlar	Linza shakli; FPD; 3D aylana uzunligi (shablon va demo linza treysingida 2D aylana); oprava egilish burchagi; oprava egriligi
O'lchash nuqtalari	1 000 nuqta
Opravani mahkamlash	Bir tugmali avtomatik mahkamlash
Stilus sozlamasi	Avtomatik va yarim avtomatik rejimlar o'rtasida almashtiriladi
Treysing vaqti: oprava	30 soniya va undan kam (kalibrlash moslamasi yordamida avtomatik binokulyar treysing)
Treysing vaqti: shablon	20 soniya va undan kam (kalibrlash moslamasi yordamida treysing)
Quvvat manbai	AC 100–120 V / 230 V, 50/60 Gts
Quvvat sarfi	70 VA
Kiritiladigan ma'lumotlar	Yo'q
Display	Yo'q
Interfeys	RS-232C: 2 ta port (1 tasi shtrix-kod skaneri uchun, 1 tasi kompyuter yoki linza stanogi uchun); USB: 1 ta port
O'lchamlari/massasi	315(K) x 300(Ch) x 155(B) mm / 7 kg (12.4 x 11.8 x 6.1" / 15 lbs.)
Standart aksessuarlar	Ehtiyot saqlagich, olti qirrali kalit, stilus g'ilofi, standart shablon, shablon o'rnatish bloki, standart oprava, oprava tayanch qo'shimchasi, Windows uchun USB drayver CD, RS-232C kabeli (3 m), USB kabeli (1 m), quvvat kabeli, chang qopqog'i
Qo'shimcha aksessuarlar	Shtrix-kod skaneri, RS-232C kabeli (5 m, 10 m), USB kabeli (3 m, 5 m)

O'lchash diapazoni

Oprava: shakl kengligi	36 dan 85 mm gacha
Oprava: shakl balandligi	18.4 dan 66 mm gacha
Oprava: gorizontal kengligi	113 dan 180 mm gacha
Oprava: qisqich o'rtasidan maksimal balandlik	23 mm

Oprava: maksimal vertikal kenglik	Maksimal balandlikda 50 mm
Oprava: maksimal gorizontal kenglik	Maksimal balandlikda 150 mm
Shablon	ø22 dan 74 mm gacha (vertikal bo'yicha 15.5 dan 66 mm gacha)

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app