

Ko'p funktsiyali linza ishlov berish stanogi ME-1



- Balandligi 11 mm gacha bo'lgan pog'onali faska
- Sport va maxsus opravalarga mukammal moslashish uchun yuqori egrilik va maxsus faska
- Ijodkorlikni ochuvchi dizayn kesish (design cut)
- Avtomatik 3D teshik ochish
- Optimallashtirilgan ishlov berish ketma-ketligi

Texnik xususiyatlari

Ishlov berish tizimi	Shablonsiz (patternless)
Rejim	Faska (bevel) hosil qilish; mini-faska (0.4 dan 0.7 mm gacha) (0.1 mm qadam); yuqori baza egriligi uchun faska; maxsus (custom) faska; pog'onali (step) faska; qisman pog'onali faska; qisman faska; tekis ishlov (flat edging); ariqcha ochish (grooving); qisman ariqcha; silliqlash (polishing); chamfer (silliqlash bilan va silliqlashsiz); maxsus xavfsiz faska; facet; dizayn kesish (design cut); teshik ochish (drilling); yumshoq ishlov (soft processing)
Abraziv g'ildirak konfiguratsiyasi	PLB-8S, PLB-2R8S turi
Suv ta'minoti tizimi	Nasos orqali aylanma yoki to'g'ridan-to'g'ri suv quvuriga ulanish
Interfeys	RS-232C: 3 ta port; LAN: 1 ta port
Quvvat manbai	AC 100–120 V / AC 200–240 V, 50/60 Gts
Quvvat sarfi	1.5 kVA
O'lchamlari/massasi	702.5(K) x 593(Ch) x 451(B) mm / 72 kg (27.66 x 23.3 x 17.8" / 159 lbs.)
Standart aksessuarlar	Shisha uchun dag'al abraziv g'ildirakni tuzatish tayoqchasi (faqat PLB-2R8S), pardoqlash g'ildiragini tuzatish tayoqchasi, silliqlash g'ildiragi uchun pasta to'plami, kalibrash moslamasi, stilus qalam, kalit, tekis linza, olti qirrali otvyorka, parma, moslashuvchan kosacha, yuqori baza egriligi uchun moslashuvchan kosacha, moslashuvchan kosachani olgich, ikki tomonlama yelimli yostiqcha, ferrit o'zak, sim bog'ich, uzaytirgich kabel (2 dona), quvvat kabeli
Qo'shimcha aksessuarlar	Shtrix-kod skaneri, aylanma nasos baki, parma (ø1.0, 1.2, 1.6)

Sozlash diapazoni

FPD (oprava markazlari masofasi)	30.00 dan 99.50 mm gacha (0.01 mm qadam)
PD (ko'zlararo masofa)	30.00 dan 99.50 mm gacha (0.01 mm qadam)
1/2PD	15.00 dan 49.75 mm gacha (0.01 mm qadam)
Optik markaz balandligi	±15.0 mm (0.1 mm qadam)
O'lchamni sozlash	±9.95 mm (0.01 mm qadam)

Eng kichik ishlov o'lchami

Tekis ishlov	ø32.0 x 19.0 mm
Faska bilan ishlov	ø33.6 x 20.6 mm
Xavfsiz faska (tekis)	ø34.0 x 21.0 mm
Xavfsiz faska (faskali)	ø35.6 x 22.6 mm
Yuqori baza egriligi uchun faska (faska balandligi 0.8 mm uchun)	ø37.9 x 24.4 mm
Ariqcha ochish	ø32.0 x 19.0 mm

Teshik ochish (drilling)

Teshik diametri	ø0.80 dan 10.00 mm gacha (0.01 mm qadam)
Teshik chuqurligi	0.1 dan 6.0 mm gacha
Teshik ochish uchun eng kichik linza diametri	7° dan kam: ø34.0 mm; 7° va undan katta: ø30.0 mm
Teshik ochish yo'nalishi	Avtomatik/qo'lda og'dirish 0 dan 30° gacha

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app