

Oldindan yuklangan torik IOL inyeksiya tizimi NexLoad NP-T



- Ajoyib aylanish barqarorligi
- Silliqlik in'ektsiya
- Oddiy ikki bosqichli jarayon
- Past diopriyalik IOL'lar ham mavjud

Texnik xususiyatlari

Mahsulot nomi	NexLoad NP Toric
Model	NP-T1, NP-T3, NP-T4, NP-T5, NP-T6, NP-T7, NP-T8, NP-T9
Yuklangan linza	Aktis Toric
Linza modeli	NS60YT1, NS60YT3, NS60YT4, NS60YT5, NS60YT6, NS60YT7, NS60YT8, NS60YT9
Silindr kuchi (IOL tekisligida)	0.75 / 1.50 / 2.25 / 3.00 / 3.75 / 4.50 / 5.25 / 6.00 D
Silindr kuchi (kornea tekisligida)	0.52 / 1.05 / 1.57 / 2.08 / 2.60 / 3.11 / 3.62 / 4.13 D (o'rtacha psevdofakik inson ko'zi bo'yicha hisoblangan)
Dioptriya diapazoni	NP-T1/T3: 1.0 dan 30.0 D gacha; NP-T4/T5/T6: 2.0 dan 30.0 D gacha; NP-T7/T8: 3.0 dan 30.0 D gacha; NP-T9: 4.0 dan 30.0 D gacha (mavjud modellar va dioptriya diapazoni mamlakatga qarab farq qiladi)
Dioptriya qadami	0.5 D qadam: 5.0 dan 27.0 D gacha; 1.0 D qadam: 1.0 dan 5.0 D gacha va 27.0 dan 30.0 D gacha
Umumiy uzunligi	13.0 mm
Optik qism diametri	6.0 mm
Optik qism materiali	Sariq tusli gidrofob yumshoq akril
Haptik qism materiali	Sariq tusli gidrofob yumshoq akril
Haptik burchak	0°
A konstanta	119.1 (faqat ma'lumot uchun; aniq parametrlar jarrohning shaxsiy tajribasi asosida belgilanishi kerak)
Kutilayotgan oldingi kamera chuqurligi	5.7 mm (faqat ma'lumot uchun)

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app