

Transfer usulida bo'yash mashinasi TTM-2000



- Qo'lda boshqarish va partiyalab ishlov berish
- NIDEK ning noyob «Dry» (quruq) bo'yash texnologiyasi qo'llaniladi

Texnik xususiyatlari

Asosiy xususiyatlar

Quvvat manbai	Uch fazali 200 V / $\pm 5\%$ o'zgarish
Chastota	50/60 Gts / $\pm 0.5\%$ o'zgarish
Yerga ulash simi	Talab qilinadi
Avtomat (breaker)	40 A
Quvvat sarfi	6.5 kVA (maks. 10.4 kVA)
Uskunaning tashqi o'lchamlari	850(K) x 970(Ch) x 1630(B) mm (anker tayanchlarsiz)
Uskuna massasi	370 kg
Ortiqcha kuchlanish toifasi	II toifa
Ifloslanish darajasi	2 (IEC60664-1)
Tovush bosimi darajasi	70 dBA va undan past (uskunaning old tomonidan 1 m masofada)
Qo'llanilishi	Ko'zoynak linzalari
Jarayon	Transfer usulida quruq bo'yash: original NIDEK siyohi bilan inkjet printerda transfer qog'ozga bosish → transfer jarayoni (sublimatsiyalangan bo'yoq transfer bo'yash mashinasida linza va asosga o'tkaziladi) → singdirish jarayoni (o'tkazilgan bo'yoq isitiladigan pechda linza va asosga singdiriladi)

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com
To'liq katalog va narx so'rash: medkatalog.vercel.app